


CUSTOM FRAMELESS LUMINOUS BARS

LINE OF ULTRA-THIN LINEAR LAMPS WITH UNIFORM LIGHT EMISSION DESIGNED TO OBTAIN AN EXTREMELY CLEAN RESULT.






TECHNICAL SPECIFICATIONS

REV00

INPUT VOLTAGE	24Vdc
DRIVER	AC DC 24V DC OUTPUT (class 2 Power Unit)
DIMMABILITY	YES by all existing systems (0-10V, Dali, DMX, ELV/MLV, Lutron Ecosystem, ...)
POWER CONSUMPTION	Standard bright 4.5 W per linear ft (14 W per linear meter) High bright 9 W per linear ft (28 W per linear meter)
LUMEN DELIVERD	Standard bright 980lm/m (315 lm/ft) High bright 1960lm/m (639 lm/ft)
IP GRADE	IP40 - suitable for Dry Location (IP54 - Damp Location under request)
CRI	> 95
WEIGHT	25 Kg/sq. mt_[5.7 lbs/sq. ft]
LIFE TIME	70.000 hrs
WARRANCY	3 Years (36 months)



SIZE




STANDARD WIDTH	15mm - 25mm - 30mm - 35mm - 40mm - 50mm - 55mm - 76mm - 100mm - 152mm - 200mm 0.6" - 1" - 1.2" - 1.4" - 1.6" - 2" - 3" - 4" - 6" - 8"
CUSTOM WIDTH	from 15mm to 200mm* from 0.6" to 8"

USE*	KELVIN**	BRIGHTNESS AND W	DIMMING	MOUNTING SYSTEM *	IP RATING	FINISH	PRINTING
CEILING	2000K	Standard bright (14 W/mt _4.5 W/ft)	NO DIMMING	NO MOUNTING SYSTEM	IP40 (DRY LOCATION)	STANDARD RAL 9010	PRINTING ON SURFACE USING A NEW UV TECHNOLOGY
	2700K						
WALL	3000K	980lm/m (315 lm/ft)	DALI	MAGNETIC	OR	STANDARD RAL 9010	(HIGH RESOLUTION FILE NEEDED)
	3500K						
FLOOR	4100K	High bright (28 W/m_9 W/ft)	DMX	STEEL CORDS	IP54 (DAMP LOCATION)	STANDARD RAL 9010	(HIGH RESOLUTION FILE NEEDED)
CABINET	5000K						
MIRROR	Tunable White 2700-6000K	1960lm/m (639lm/ft)	ELV/MLV	UPLIGHT	IP54 (DAMP LOCATION)	STANDARD RAL 9010	(HIGH RESOLUTION FILE NEEDED)
	Tunable White 2400-4100K						
	RGB		LUTRON ECOSYSTEM				


*Promotech reserves the right to modify and advise in case the dimension of the panel doesn't allow to use the system selected.

** Other Kelvin, Dim to Warm, RGBW and RGBTW under request.


NO FIXING SYSTEM



STEEL CORDS - SUSPENDED




MAGNETIC SURFACE



THICKNESS 22,5mm STANDARD WIDTH	<ul style="list-style-type: none"> • 15mm - 25mm - 30mm - 35mm - 40mm - 50mm - 55mm - 76mm - 100mm - 152mm - 200mm • 0.6" - 1" - 1.2" - 1.4" - 1.6" - 2" - 3" - 4" - 6" - 8" • the measurements given above +4mm (+0,15in) is considered standard width. For other measure see the custom width
THICKNESS 23mm CUSTOM WIDTH	<ul style="list-style-type: none"> • other widths than the standard ones



CABLE EXIT



- A - SIDE_short size
- B - BACK
- C - SIDE_long size

<42W: 1 CABLE

>42W: 2 CABLES

Cables ~500mm(20") + Extension cables ~1000mm(40")
custom length of cables under request.